

LED HIGH BAY G3

APPLICATIONS : Warehouse, Plant, Supermarket, Storage Room, Workshop, Stadium etc.



Designed by Japanese




- ✓ HIGH QUALITY LED CHIP
- ✓ HIGH PERFORMANCE AND DURABLE
- ✓ EXCELLENT HEAT SINK
- ✓ ENERGY SAVING MORE THAN 50%
- ✓ LONG LIFE SPAN




SPECIFICATION

PRODUCT MODEL	HB03-100N	HB03-120N	HB03-150N	HB03-200N	HB03-250N
POWER	100W	120W	150W	200W	250W
LUMEN	16,900 LM	19,800 LM	24,000 LM	31,200 LM	38,000 LM
LUMEN/WATT	169 LM/W	165 LM/W	160 LM/W	156 LM/W	152 LM/W
INPUT VOLTAGE	AC100-240V, 50-60 HZ				
SURGE PROTECTION	SURGE IMMUNITY LINE-EARTH 4KV, LINE-LINE 2KV				
POWER FACTOR	PF > 0.95 +/- 2%				
OPERATION TEMPERATURE	-40°C TO 70°C				
COLOR TEMPERATURE (CCT)	3,000 - 6,500 K				
COLOR RENDERING (RA)	CRI > 80				
MATERIAL	ALUMINIUM + CU				
BEAM ANGLE	60° / 120°				
IP RATE	IP 65				
THDI (%)	< 10%				
LIFE TIME	50,000 HRS				
DIMENSION (ØAXB MM)	Ø460X340	Ø460X340	Ø460X390	Ø460X410	Ø460X460
WEIGHT	3.5 KG	3.5 KG	4.3 KG	5 KG	5.9 KG


DIMENSION



PHOTOMETRIC DATA



BEAM ANGLE 60°



BEAM ANGLE 120°



LEDsave

LEDsave (THAILAND) CO.,LTD.

15/16 Moo18 Bangphli-Yai, Bangphli, Samutprakan 10540



TEL. 02-045-4768-9



www.facebook.com/LEDsave



admin@ledsave.co.th



FAX. 02-045-3884-5



@ledsave



www.ledsave.co.th



LINE : @LEDsave